



PCB TERMINAL BLOCKS

5.08mm Pitch 45° Rising Clamp Terminal Blocks

- 2 & 3 pole interlocking
- 4-12 pole pre-assembled
- 45° mounting
- Moulded in grey UL94-V0 flame retardant PA
- Professional rising clamp terminals
- 0.2-4.0mm² (30-12AWG) solid cable
- 0.2-2.5mm² (30-12AWG) stranded cable
- Captive screw
-  approved

CTB3008



SPECIFICATION

| | |
|---------------------------|---|
| Rating | 24A/160V UL=16A/300V, VDE&IMQ=24A/130V |
| Dielectric strength | ≥1.25kV |
| Impulse withstand voltage | 2.5kV |
| Working temperature | 110°C |
| Moulding | UL94-V0 flame retardant PA |
| Pin/terminal | Tinned, nickel plated brass |
| Rising clamp | Tinned, nickel plated brass |
| Screw/torque | M3 steel zinc plated, 0.5Nm |
| Recommended PCB hole size | ø1.3mm |

| TYPE NO. | POLES | LENGTH |
|------------|-------|---------|
| CTB3008/2 | 2 | 10.16mm |
| CTB3008/3 | 3 | 15.24mm |
| CTB3008/4 | 4 | 20.32mm |
| CTB3008/5 | 5 | 25.4mm |
| CTB3008/6 | 6 | 30.48mm |
| CTB3008/7 | 7 | 35.56mm |
| CTB3008/8 | 8 | 40.64mm |
| CTB3008/9 | 9 | 45.72mm |
| CTB3008/10 | 10 | 50.8mm |
| CTB3008/11 | 11 | 55.88mm |
| CTB3008/12 | 12 | 60.96mm |

